



GLO PRO-1212

FEATURES

- Made of Dow Chemical SILASTIC™ ET-7021 silicone rubber, which
- Provides high transparency and high strength
- Environmental protection grade silicone material
- Integrated extrusion molding process
- Unique optical light distribution structure design, uniform lighting surface and no shadow;
- IP67 protection level, salt solution resistance, acids & alkali and UV resistance
- Excellent toughness, simple and stylish appearance, delicate and unique;
- 5 years warranty, working life ≥ 30000 hours
- Customizable for low-voltage operation suitable for car lift applications



SPECIFICATION

Basic Parameters

Size	12mm x 12mm x costum length
Max Power	10W/1m or 50W/5m
Continuous Max Run	10 meters
Lifetime	>30,000 hours
Input Voltage	DC24V
Colour/CCT	2700K, 3000K, 4000K, 6500K, RGB, RGB+CCT
CRI	>90
IP Rating	IP67
Energy Efficiency Class	>A+
Warranty	5 years/30,000 hours
Control	Phase cut, leading & trailing/ 0-10V/1-10V/DMX/DALI
Beam Angle	60°, 90°, 170°, Beam

Product Ordering

CODE	LM-M	COLOUR	STOCKED
GLOPRO-24-1212-2700-67	820	2700K	YES
GLOPRO-24-1212-3000-67	900	3000K	YES
GLOPRO-24-1212-4000-67	980	4000K	YES
GLOPRO-24-1212-6500-67	1000	6500K	YES
GLOPRO-24-1212-RGB-67	620-630nm	RGB	S/O
GLOPRO-24-1212-RGB+CCT-67	520-530nm	RGB+CCT	S/O

